

### Amendments to Claims

Please amend the claims as follows:

Claim 1. (currently amended) A system for evaluating the condition of an item, the system comprising the components of:

a sensor chamber including an interior area for housing an evaluation item, the interior area including a plurality of sensors associated to the sensor chamber;

a controller that is communicatively coupled to the plurality of sensors and operative to control the operation of the plurality of sensors and obtain data readings from the plurality of sensors while the evaluation item is located within the sensor chamber;

an information acquisition engine operable to receive information regarding the evaluation item;

a database containing expected results pertaining to the evaluation item; and

a damage calculator that is operable to compare the data readings from the plurality of sensors and the expected results from the database to identify particular characteristics pertaining to the evaluation item.

Claim 2. (currently amended) The system of claim 1, further comprising a console and, wherein the information acquisition engine is operable to receive information regarding the evaluation item provided by an operator using ~~from~~ the console.

Claim 3. (original) The system of claim 1, further comprising a network interface and, where the information acquisition engine is operable to receive information regarding the evaluation by ~~searching for information through the network interface, identifying sources for information and~~ extracting the information.

Claim 4. (original) The system of claim 3, wherein the network interface provides access to a manufacturing and industry data source.

Claim 5. (original) The system of claim 1, further comprising a document capture device and wherein the information acquisition engine is operable to receive information regarding the evaluation item through the document capture device.

Claim 6. (original) The system of claim 1, wherein the controller is operable to initially control the plurality of sensors to obtain evaluation item identification information and, based at least in part on the evaluation item identification information, is operative to control the plurality of

sensors to obtain data readings from the plurality of sensors based at least in part on the evaluation item identification information.

Claim 7. (original) The system of claim 6, wherein the database includes a plurality of control sequences and, the controller is operative to initially control the plurality sensors based on a particular control sequence selected from the plurality of control sequences.

Claim 8. (original) The system of claim 6, wherein the database includes a plurality of control sequences and, the controller is operative to control the plurality sensors to obtain data readings based on a particular control sequence selected from the plurality of control sequences based at least in part on the evaluation item identification information.

Claim 9. (original) The system of claim 1, wherein the sensor chamber includes a plurality of environmental controls and wherein the controller is further operative to control the state of the environmental controls.

Claim 10. (original) The system of claim 6, wherein the sensor chamber includes a plurality of environmental controls and wherein prior to controlling the plurality of sensors to obtain data readings the control sets the state of the environmental controls based at least in part on the evaluation item identification information.

Claim 11. (currently amended) A system for evaluating the condition of an item, the system comprising the components of:

a sensor chamber including an interior area for housing an evaluation item, the interior area including a plurality of sensors;

---

a controller that is communicatively coupled to the plurality of sensors and operative to control the operation of the plurality of sensors and obtain data readings from the plurality of sensors, wherein the controller is operable to detect when the evaluation item is placed into the interior of the sensor chamber;

an information acquisition engine operable to receive information regarding the evaluation item;

a database containing expected results pertaining to the evaluation item; and

a damage calculator that is operable to compare the data readings from the plurality of sensors and the expected results from the database to identify particular characteristics pertaining to the evaluation item~~The system of claim 1.~~

Claim 12. (currently amended) A computer implemented method of performing an evaluation for an item placed into a sensor chamber that includes a plurality of sensors, the evaluation assisting a decision maker in a decision regarding the condition of the item when the decision maker does not have direct access to the item, the method comprising the steps of:

detecting the presence of an evaluation item entered into a sensor chamber by examining the plurality of sensors;

executing a first sensor sequence to identify the evaluation item;

based on the identification of the evaluation item, adjust the ambient environment condition of the sensor chamber and execute a second sensor sequence to obtain sensor sequence result data;

comparing the sensor sequence result data to a set of expected data, the set of expected data selected at least in part on the results of executing the first sensor sequence; and

identify any particular characteristics of the evaluation item based on differences between the sensor sequence result data and the set of expected data.

Claim 13. (original) The method of claim 12, where in prior to executing the first sensor sequence, the method includes the step of entering preliminary data pertaining to the evaluation item, the preliminary data being operative to assist in identifying the item.

Claim 14. (original) The method of claim 13, wherein the first sensor sequence utilized in the step of executing the first sensor sequence is selected based at least in part on at least a portion of the preliminary data.

---

~~Claim 15. (original) The method of claim 14, wherein the second sensor sequence is selected from a plurality of sensor sequences based at least in part on the results of executing the first sensor sequence.~~

Claim 16. (original) The method of claim 12, wherein the second sensor sequence is selected from a plurality of sensor sequences based at least in part on the results of executing the first sequence.

Claim 17. (original) The method of claim 12, wherein the sensors in the sensor chamber can be moved and the step of adjusting the ambient environment condition of the sensor chamber further comprises the step of moving the sensors based at least in part on the results of executing the first sensor sequence.

**BEST AVAILABLE COPY**

Claim 18. (original) The method of claim 12, wherein the expected data includes manufacturing and industry data pertaining to the evaluation item and the step of comparing sensor sequence result data to a set of expected data includes the steps of:

accessing the manufacturing and industry data based on the results of executing the first sensor sequence; and

comparing the sensor sequence result data to the manufacturing and industry data.

Claim 19. (original) The method of claim 12, further comprising the step of classifying the particular characteristics into one of a plurality of classes.

Claim 20. (currently amended) A system for evaluating the condition of an item to assist in making a decision regarding the item, the system comprising the components of:

a sensor chamber including an interior area for housing an evaluation item, the interior area including a plurality of electronically adjustable and electronically moveable sensors and a plurality of environmental controls that are associated with the sensor chamber;

an information acquisition engine operable to receive information regarding the evaluation item;

a controller that is communicatively coupled to the plurality of sensors and environmental controls and operable to:

initially control the operation of the plurality of sensors and, in conjunction with any information obtained from the information acquisition engine, to identify the evaluation item;

---

~~in response to identifying the evaluation item, control the operation of the~~  
plurality of environment controls to establish an environmental setting within the sensor chamber that is conducive for further evaluation of the evaluation item; and

further control the operation of the plurality of sensors to move the sensors to an optimal position and obtain data readings from the plurality of sensors;

a database containing expected results pertaining to the evaluation item; and

a damage calculator that is operable to compare the data readings from the plurality of sensors and the expected results from the database to identify particular characteristics pertaining to the evaluation item.

**BEST AVAILABLE COPY**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**